

Utskriftsdatum 2024-10-22
Giltigt till och med 2025-10-21

M290300070300	Freshcling ECO refill 4130300
M290300070403	ECO Champagne refill 4130300-H
M290600080300	Freshcling ECO refill 95353
M440300070300	Freshcling ECO refill 4145300
M440300070403	ECO Champagne refill 4145300-H
M440600080300	Freshcling ECO refill 95354
M600300080300	Freshcling ECO refill 4160300R
N290300080600	Freshcling ECO box 4130300-B
N440300080600	Freshcling ECO box 4145300-B

is produced under Quality and Hygiene certified Management System:

- Quality: **ISO 9001** by Lloyds
- Hygiene: **BRC/IoP** Hygiene Standards including HACCP by Lloyds
- Environment: **ISO 14001** by Lloyds

1. We confirm that this product fulfils the requirements on materials used for articles or component of articles intended to come into contact with food as described in the following European and Dutch legislation :

- Framework Regulation (EC) N° 1935/2004
- G.M.P Regulation (EC) N° 2023/2006
- Regulation (EU) N° 10/2011 (up to and including the amendment 2015/174/EC)
- Dutch Regulation Verpakkingen- en Gebruiksartikelen (Warenwet)
- Reach EC1907-2006 and amendments.

1a. This film does not contain no SVHC substances neither in article nor in packing materials

2. Additive(s) and/or monomer(s) are listed in the positive list of regulation (EU) N° 10/2011 and amendment

3. NIAS: Potential Non intentional Added Substances are under ongoing risk assessment using recognized method.

4. Substance(s) with Specific Migration Limit :

The above film could contain an additive or a monomer that has specific migration limit restriction. In referring to the food contact certificates provided by our suppliers, we are confident that the total additives level in this film is below the limit (we check that this/these substance(s) meet(s) the limits by worst case calculation or with the help of migration tests).

Monomer / Additive	PM Ref.	Specific Migration Limit(s) (ppm):
Adipic acid, bis(2-ethylhexyl) ester	31920	18
Polyesters of 1,2-propanediol and/or 1,3- and/or 1,4-butanediol and/or polypropyleneglycol with adipic acid, also end-capped with acetic acid or fatty acids C12-C18 or n-octanol and/or n-decanol	76866	30
ESBO, modified octadecyl	00240	50

ESBO, epoxidised soybean oil	8884U	6U
VCM, vinyl chloride monomer	26050	0.01
Zn	/	25

5. The overall migration and specific migration limits have been checked on the finished articles representing the

6. Therefore this film is complying with the following application :

- Any long term storage at room temperature or below:
- Including heating up to 70°C for up to 2 hours, or heating up to 100°C for up to 15 minutes.

7. Dual use additives

To the best of our knowledge based on supplier's declaration and /or confidentiality requirements, this product contains:

Dual used Additive	PM Ref.	E-number	Conc. Maxi (ppm)
None	None	none	None

8. We have implemented a traceability system as requested from Art. 17 Regulation (EC) N°1935/2004 via the number on the box/number on core in conjunction with the date of production.


9. We hereby confirm that we do not use intentionally for the production of our films:

- Phthalates
- BADGE, NODGE & BFDGE
- BPA (Bisphenol A)

9a. We declare that we do not use the following substance(s) as raw materials or processing aids for the production of our films)

- Nano materials

10. The above film is suitable for wrapping foodstuffs as examples described below:




Margarine and butter



Cheese



Meat




Fish



Sandwich



Fruit, vegetable and frozen product




Micro-wave oven
For defrosting and reheating.
Avoid direct contact with food.




Freezer (subject to individual trials)

Migration tests carried out in distilled water at 100°C for 1 hour.

AllOffice Nordic AB



Pure fat and oil, food preserved in an oily medium



Traditional oven, infrared oven and multi purpose oven

11. Labeling

Rules on labeling:

This product is labeled "for food contact".

or

This product bears the glass-fork symbol as illustrated below:



11. Warehouse rules:

Optimal storage conditions: 15/20°C away from humidity. Film properties may be altered in extreme storage conditions.

The recipient should pay particular attention to any change in the packaged product, its intended use and also to any modification in the material's processing conditions and make sure that the contents and packaging are compatible, as directed in this declaration.

This certificate is only valid when the film is used in normal and foreseeable conditions, provided that the handling and storage conditions are also appropriate for preservation of the material's specific characteristics.

12. The present declaration is valid 3 years after the date of its issue provided no new regulation comes in force and no modification of the product likely to modify the specifications is made during that period.